

# WhiteWater

PRODUCT  
DATA SHEET  
**C-150**

INDUSTRY-PROVEN OZONE CLEANING & SANITIZING SYSTEMS

<b>Flow Capacity</b>	30 GPM @ 2 PPM dissolved ozone (Light soil environments) 15 GPM @ 5 PPM dissolved ozone (Heavy soil environments)
<b>Advanced Features</b>	Skid mounted Safety interlocks and diagnostic indicators Stainless steel pump
<b>Installation</b>	Centralized
<b>Electrical Requirement</b>	240 VAC, 20 Amps
<b>Water Requirement</b>	40 PSI @ 15-30 GPM
<b>Water Connections</b>	1.25" FPT Supply 1.25" FPT Process header
<b>Dimensions</b>	32"W x 50"L x 74"H
<b>Weight</b>	225 lbs (empty), 550 lbs (full tank)



SYSTEM CAPABILITIES	Low Pressure Sanitizing	Low Pressure Spray Bar Treatable Belt Width	Low Pressure Spray Stations	DualStream™ High+Low Pressure Cleaning & Sanitizing	DualStream™ Spray Bar Treatable Belt Width	DualStream™ Spray Stations
	Light Soil Environments	✓	425"	10	✓ with HP-75	33"
✓ with HP-150					71"	5
Heavy Soil Environments	✓	210"	5	✓ with HP-75	33"	1
				✓ with HP-150	71"	2

Instantaneous total flow demand by low pressure spray bars, low pressure spray stations, high+low pressure spray bars, and high+low pressure spray stations must not exceed system capacity. System capabilities can vary based on plant operating conditions, piping, spray nozzle selection/placement, and other factors.

**Questions? Call (888) 780-5552 or visit [www.o3international.com](http://www.o3international.com).**



**Ozone International**  
Industry-Proven Ozone Cleaning and Sanitizing Systems

Phone: (888) 780-5552  
Fax: +1 (206) 780-5554  
[www.o3international.com](http://www.o3international.com)