

WhiteWater

PRODUCT
DATA SHEET
C-1500

INDUSTRY-PROVEN OZONE CLEANING & SANITIZING SYSTEMS

Flow Capacity	175 GPM @ 2 PPM dissolved ozone (Light soil environments) 150 GPM @ 5 PPM dissolved ozone (Heavy soil environments)
Advanced Features	Advanced PLC control Remote monitoring Maximum efficiency single pump design
Installation	Centralized
Electrical Requirement	480 VAC, 70 Amps
Water Requirement	40 PSI @ 150-175 GPM
Water Connections	3" FPT Supply 3" FPT Process loop
Dimensions	48"W x 70"L x 84"H
Weight	1200 lbs (empty), 4000 lbs (full tank)



SYSTEM CAPABILITIES	Low Pressure			DualStream™		
	Sanitizing	Spray Bar Treatable Belt Width	Spray Stations	High+Low Pressure Cleaning & Sanitizing	Spray Bar Treatable Belt Width	Spray Stations
Light Soil Environments	✓	2,500"	58	✓ with HP-700	333"	23
				✓ with HP-1500	713"	50
				✓ with HP-2200	1,045"	58
Heavy Soil Environments	✓	2,140"	50	✓ with HP-700	333"	10
				✓ with HP-1500	713"	21
				✓ with HP-2200	1,045"	31

Instantaneous total flow demand by low pressure spray bars, low pressure spray stations, high+low pressure spray bars, and high+low pressure spray stations must not exceed system capacity. System capabilities can vary based on plant operating conditions, piping, spray nozzle selection/placement, and other factors.

Questions? Call (888) 780-5552 or visit www.o3international.com.



Ozone International
Industry-Proven Ozone Cleaning and Sanitizing Systems

Phone: (888) 780-5552
Fax: +1 (206) 780-5554
www.o3international.com