

# WhiteWater

PRODUCT  
DATA SHEET  
**C-300**

INDUSTRY-PROVEN OZONE CLEANING & SANITIZING SYSTEMS

**Flow Capacity** 60 GPM @ 2 PPM dissolved ozone  
(Light soil environments)  
30 GPM @ 5 PPM dissolved ozone  
(Heavy soil environments)

**Advanced Features** Skid mounted  
Safety interlocks and diagnostic indicators  
Stainless steel pump

**Installation** Centralized

**Electrical Requirement** 480 VAC, 20 Amps

**Water Requirement** 40 PSI @ 30-60 GPM

**Water Connections** 1.25" FPT Supply  
1.25" FPT Process header

**Dimensions** 34"W x 60"L x 77"H

**Weight** 225 lbs (empty), 550 lbs (full tank)



SYSTEM CAPABILITIES	Low Pressure Sanitizing	Low Pressure Spray Bar Treatable Belt Width	Low Pressure Spray Stations	DualStream™ High+Low Pressure Cleaning & Sanitizing	DualStream™ Spray Bar Treatable Belt Width	DualStream™ Spray Stations
	Light Soil Environments	✓	855"	20	✓ with HP-150	71"
✓ with HP-350					166"	11
Heavy Soil Environments	✓	425"	10	✓ with HP-150	71"	2
				✓ with HP-350	166"	5

Instantaneous total flow demand by low pressure spray bars, low pressure spray stations, high+low pressure spray bars, and high+low pressure spray stations must not exceed system capacity. System capabilities can vary based on plant operating conditions, piping, spray nozzle selection/placement, and other factors.

**Questions? Call (888) 780-5552 or visit [www.o3international.com](http://www.o3international.com).**



**Ozone International**  
Industry-Proven Ozone Cleaning and Sanitizing Systems

Phone: (888) 780-5552  
Fax: +1 (206) 780-5554  
[www.o3international.com](http://www.o3international.com)