

WhiteWater

PRODUCT
DATA SHEET
HP-350

INDUSTRY-PROVEN OZONE CLEANING & SANITIZING SYSTEMS

Flow Capacity	35 GPM @ 1500 PSI
Advanced Features	Efficient and reliable Giant pump Integrated timer and shutdown circuit
Installation	Centralized
Electrical Requirement	480 VAC, 70 Amps with separate 115 VAC, 15 Amp Control Ckt.
Water Requirement	40 PSI @ 35 GPM
Water Connections	1" FPT Supply 1" FPT High pressure header
Dimensions	27"W x 76"L x 72"H
Weight	850 lbs (empty), 2550 lbs (full tank)



SYSTEM CAPABILITIES	DualStream™ High+Low Pressure Cleaning & Sanitizing	DualStream™ Spray Bar Treatable Belt Width	DualStream™ Spray Stations
	Light Soil Environments	✓ with C-250	166"
✓ with C-500		166"	11
✓ with C-1000		166"	11
Heavy Soil Environments	✓ with C-250	166"	5
	✓ with C-500	166"	5
	✓ with C-1000	166"	5

Instantaneous total flow demand by low pressure spray bars, low pressure spray stations, high+low pressure spray bars, and high+low pressure spray stations must not exceed system capacity. System capabilities can vary based on plant operating conditions, piping, spray nozzle selection/placement, and other factors.

Questions? Call (888) 780-5552 or visit www.o3international.com.



Ozone International
Industry-Proven Ozone Cleaning and Sanitizing Systems

Phone: (888) 780-5552
Fax: +1 (206) 780-5554
www.o3international.com