

WhiteWater

PRODUCT
DATA SHEET
HP-75

INDUSTRY-PROVEN OZONE CLEANING & SANITIZING SYSTEMS

Flow Capacity	7.5 GPM @ 1500 PSI
Advanced Features	Efficient and reliable Udor pump Integrated timer and shutdown circuit
Installation	Centralized
Electrical Requirement	240 VAC, 40 Amps
Water Requirement	40 PSI @ 10 GPM
Water Connections	.75" FPT Supply .75" FPT High pressure header
Dimensions	24"W x 36"L x 36"H
Weight	600 lbs



SYSTEM CAPABILITIES	DualStream™ High+Low Pressure Cleaning & Sanitizing	DualStream™ Spray Bar Treatable Belt Width	DualStream™ Spray Stations
Light Soil Environments	✓ with C-50	33"	2
	✓ with C-150	33"	2
Heavy Soil Environments	✓ with C-50	33"	1
	✓ with C-150	33"	1

Instantaneous total flow demand by low pressure spray bars, low pressure spray stations, high+low pressure spray bars, and high+low pressure spray stations must not exceed system capacity. System capabilities can vary based on plant operating conditions, piping, spray nozzle selection/placement, and other factors.

Questions? Call (888) 780-5552 or visit www.o3international.com.



Ozone International
Industry-Proven Ozone Cleaning and Sanitizing Systems

Phone: (888) 780-5552
Fax: +1 (206) 780-5554
www.o3international.com