

WhiteWater

PRODUCT
DATA SHEET
M-35

INDUSTRY-PROVEN OZONE CLEANING & SANITIZING SYSTEMS

Flow Capacity	3.3 GPM @ 2 PPM dissolved ozone
Advanced Features	Stainless Steel NEMA 4X Enclosure Automatic Plug and Play Operation
Installation	Mobile
Electrical Requirement	115 VAC, 7 Amps
Water Requirement	40 PSI @ 4 GPM
Water Connections	.75" female hose thread
Dimensions	22"W x 50"L x 37"H
Weight	125 lbs



SYSTEM CAPABILITIES	Low Pressure Sanitizing	Low Pressure Spray Bar Treatable Belt Width	Low Pressure Spray Stations	DualStream™ High+Low Pressure Cleaning & Sanitizing	DualStream™ Spray Bar Treatable Belt Width	DualStream™ Spray Stations
Light or Heavy Soil Environments	✓	45"	1			

Instantaneous total flow demand by low pressure spray bars, low pressure spray stations, high+low pressure spray bars, and high+low pressure spray stations must not exceed system capacity. System capabilities can vary based on plant operating conditions, piping, spray nozzle selection/placement, and other factors.

Questions? Call (888) 780-5552 or visit www.o3international.com.



Ozone International
Industry-Proven Ozone Cleaning and Sanitizing Systems

Phone: (888) 780-5552
Fax: +1 (206) 780-5554
www.o3international.com